

Features



- Widely used in the ventilation system to heat the supply air.
- Made of ceramic PLC heater, casing consists of steel sandwiched with insulation glass wool.
- Equipped with control system, temperature can be set and adjust automatically, energy saving and comfortable.
- Easy to install and operate, free of maintenance.

Specifications

Model	Airflow	Pressure drop	Temperature rise		Power		Dimension			Duct size	Volt.	Weight
	m3/h		Pa	(°C)		(Kw)		(mm)				
HR-06	600	14	5	10	1	2	492	370	370	Φ194	220	5
HR-10	1000	17	6	12	2	4	492	370	370	Φ242	220	8
HR-16	1600	28	4.5	9	2.4	4.8	500	470	210	320x160	220	10
HR-20	2000	35	5.5	11	3.6	7.2	500	470	210	320x160	380	11
HR-26	2600	30	4.2	9.8	3.6	8.4	500	470	300	320x250	380	15
HR-30	3000	38	3.7	11	3.6	10.8	500	470	300	320x250	380	17
HR-40	4000	45	5.5	11	7.2	14.4	500	470	300	320x250	380	20
HR-50	5000	65	4.4	10.2	7.2	16.8	500	550	350	500x300	380	35
HR-75	7500	87	7.3	11.7	18	28.8	500	550	450	500x400	380	51
HR-100	10000	108	5.5	9.9	18	32.4	500	680	450	630x400	380	75
HR-150	15000	155	4.4	9.5	21.6	46.8	500	680	500	630x500	380	90